ALFOTECH



Hygienic ball valve with ISO weld end

Application:

Sanitary ball valve developed for demanding processes and sensitive media within food processing, cosmetics or in the chemical industry.

The ball valve has a full passage and can therefore be used in connection with PIG cleaning systems.

Compact size with smooth easy-to-clean surface.

Construction:

- Module built and easy to service
- Can be delivered with connection for flush function and integration to CIP system
- Can be delivered with connection for heating,
 but not at the same time as the cleaning
 function
- Straight with weld ends, other connections are possible
- Prepared for actuator connection
- Full passage

Quality:

Parts in contact with media are made of stainless steel AISI 316. Other parts made of AISI 304. Gaskets

Alfotech ApS Alstrup Allé 10 8361 Hasselager Danmark **Contact us**

Phone: +45 7020 0422

Inquiry: foresporgsel@alfotech.dk
Order: orders@alfotech.dk

VAT: 26869617

ALFOTECH



consist of parts made of the material types EPDM, PTFE, and FKM.

Standard:

FDA-approved.

Operating conditions:

- The temperature ranges up to +90°C
- Can be sterilized for up to 30 minutes at max.
 +130°C
- Pressure: Max. 10 bar

Item number	Nominal dim. mm.	D1 dia. mm.	D2 dia. mm.	Dia. mm. D4	Indbygningsmål H1 - mm.	Installation dim. L1 mm.	Installation dim. L2 mm	Elastomer type	Weight /mtr. kg.	Ва
0542264038	38,1	34,8	38,1	112,0	125,0	100,0	140,5	PTFE/EPDM	4,9	
0542264051	50,8	47,5	50,8	130,0	137,0	120,0	171,0	PTFE/EPDM	7,3	
0542264064	63,5	60,2	63,5	155,0	149,5	136,0	171,0	PTFE/EPDM	11,9	
0542264076	76,2	72,9	76,2	175,0	179,0	168,0	217,0	PTFE/EPDM	18,4	
0542264102	101,6	97,4	101,6	210,0	197,0	200,0	217,0	PTFE/EPDM	28,5	

Address

Alfotech ApS Alstrup Allé 10 8361 Hasselager Danmark **Contact us**

Phone: +45 7020 0422

Inquiry: foresporgsel@alfotech.dk
Order: orders@alfotech.dk

VAT: 26869617

ALFOTECH